REPORT DOCUMENTATION PAGE

Form Auproved
OMB No. 0704-0188



AD-A238 666

is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, ng and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this ig this burden. to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson I to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

REPORT DATE March 30, 1991

3. REPORT TYPE AND DATES COVERED

Final Report, June 1986 - Feb. 1991

5. FUNDING NUMBERS

Spline Instability in High Speed Rotors

6. AUTHOR(S)

Jorgen L. Nikolajsen

DAAL03-86-K-0096

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Texas A&M University Mechanical Engineering Dept. College Station, TX 77843-3123 8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

U. S. Army Research Office

P. O. Box 12211

Research Triangle Park, NC 27709-2211

10. SPONSORING / MONITORING AGENCY REPORT NUMBER

ARO 23288.2-E6

11. SUPPLEMENTARY NOTES

The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

12a. DISTRIBUTION / AVAILABILITY STATEMENT

12b. DISTRIBUTION CODE

Approved for public release; distribution unlimited.

13. ABSTRACT (Maximum 200 words)

Stiffness and damping coefficients have been identified experimentally for loose spline couplings used in high speed rotating machinery. This is believed to be the first time such coefficients have ever been identified experimentally. Loose spline couplings have a destabilizing effect on rotor systems. The spline coefficients are therefore needed at the machinery design stage to predict whether the rotor system will remain stable, within its operating envelope, when fitted with a particular spline coupling design.

91-05285

14. SUBJECT TERMS

Loose Spline Couplings, Rotor Stability

15. NUMBER OF PAGES

17. SECURITY CLASSIFICATION

UNCLASSIFIED

OF REPORT

18. SECURITY CLASSIFICATION
OF THIS PAGE

19. SECURITY CLASSIFICATION OF ABSTRACT

20. LIMITATION OF ABSTRACT

UNCLASSIFIED

UNCLASSIFIED

16. PRICE CODE

NSN 7540-01-280-5500

17 021

Standard Form 298 (Rev 2-89: Prescribed by ANSI 5td 239-18 298-102

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

- Block 1. Agency Use Only (Leave blank).
- **Block 2.** Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.
- Block 3. <u>Type of Report and Dates Covered.</u> State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).
- Block 4. <u>Title and Subtitle</u>. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.
- Block 5. <u>Funding Numbers</u>. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract PR - Project
G - Grant TA - Task
PE - Program WU - Work Unit
Element Accession No.

Block 6. <u>Author(s)</u>. Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

- **Block 7.** <u>Performing Organization Name(s) and Address(es)</u>. Self-explanatory.
- Block 8. <u>Performing Organization Report</u>
 <u>Number</u>. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.
- Block 9. <u>Sponsoring/Monitoring Agency Name(s)</u> and <u>Address(es)</u>. Self-explanatory.
- **Block 10.** <u>Sponsoring/Monitoring Agency</u> <u>Report Number.</u> (If known)
- Block 11. <u>Supplementary Notes</u>. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. <u>Distribution/Availability Statement</u>. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

 DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank. NTIS - Leave blank.

- **Block 13.** Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.
- **Block 14.** Subject Terms. Keywords or phrases identifying major subjects in the report.
- **Block 15.** <u>Number of Pages</u>. Enter the total number of pages.
- **Block 16.** <u>Price Code</u>. Enter appropriate price code (NTIS only).
- Blocks 17. 19. <u>Security Classifications</u>. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.
- Block 20. <u>Limitation of Abstract</u>. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same estaport). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

SPLINE INSTABILITITY IN HIGH SPEED ROTORS

Final Report

Jorgen L. Nikolajsen

March 30, 1991

U.S. ARMY RESEARCH OFFICE

Contract Number DAAL@3-86-K-@@96

TEXAS A&M UNIVERSITY

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED

Arabasica son

Eli Bria Tab

Drio Tab

Drio Tab

Comment with

Figure 1 of the control

Event and or control

Figure 1 of the control

Figure 1 of



Statement of Problem Studied

Loose spline couplings are used to transmit torque, for example between the power turbine shaft and the reduction gearbox in a gasturbine engine. However, loose splines have a destabilizing effect on the rotor systems in which they are included. objective of this work is to identify the stiffness and damping coefficients of loose splines for use in rotor stability analyses at the design stage. The spline stiffness and damping coefficients are identified by incorporating the spline in a flexible rotor system and using experimental modal analysis to measure the vib. alion characteristics of the rotor system, i.e., damped natural frequencies, mode shapes, and modal damping. A computer program is also set up to predict those same vibration characteristics of the rotor. Identification of the spline coefficients is then achieved by adjusting the coefficient values in the computer program to provide a perfect fit between the predicted and the measured vibration charateristics.

Summary of Most Important Results

Stiffness and damping coefficients have been identified for several different spline geometries showing the effect of spline diameter and length and number of teeth on the coefficient values. Spline coefficients have also been identified for several different operating conditions such as rotor speed, torque transmitted, rotor misalignment and level of spline lubrication. The coefficients are tabulated and shown in graphical form with error bounds in Publication #3, referenced in this report. Publication #3 will be forwarded to the ARO in May, 1991.

This project represents the first attempt ever to identify loose spline coupling coefficients experimentally. Publication #3 also provides recommendations for adjusting the experimental procedure to improve the accuracy of the coefficient values. However, the coefficient values shown in Publication #3 are considered adequate for rough preliminary design studies of advanced turbomachinery rotordynamics if used with due caution.

Publication of these results in a scientific journal is anticipated in the near future. The expected long term impacts of this work are (1) a wider use of simple, reliable, inexpensive spline couplings in turbomachinery and (2) retrofit of existing unstable machinery with 'stable' splines.

Publications and Technical Reports Published

- 1. Rombado, G., "Development of Experimental Apparatus and Procedures for Measurement of Rotordynamic Coefficients of Loose Spline Couplings", M.S. Thesis, Texas A&M University, May 1989.
- 2. Nikolajsen, J.L., Rombado, G., and Park, S.K., "Identification of Loose Spline Couplings. Part 1 Experimental Apparatus", The Intermational Sumposium on Advanced Computers for Dynamics and

Design, Tsuchiura, Japan, Sept. 1989.

3. Park, S.K., "Determination of Loose Spline Coupling Coefficients of Rotor-Bearing Systems in Turbomachinery", PhD Dissertation, Texas A&M University, May 1991.

Participating Scientific Personnel

Jorgen L. Nikolajsen, P.I.

Sang K. Park, earned PhD in Mechanical Engineering

Gabriel Rombado, earned M.S. in Mechanical Engineering

Reportable Inventions

None.